



CERTSWARRIOR

# Dell EMC DES-5122

**Dell EMC PowerSwitch Campus Networking Specialist  
Exam for Implementation Engineer**

**Questions&AnswersPDF**

**ForMoreInformation:**

**<https://www.certswarrior.com/>**

## **Features:**

- 90DaysFreeUpdates
- 30DaysMoneyBackGuarantee
- InstantDownloadOncePurchased
- 24/7OnlineChat Support
- ItsLatestVersion

# Latest Version: 6.0

## Question: 1

Which command should a network administrator use to configure a group of interfaces on a Dell EMC N4000 Series switch?

Response:

- A. interface tengigabitethernet 1/0/1-8
- B. interface range tengigabitethernet 1/0/1, 1/0/8
- C. interface range tengigabitethernet 1/0/1-8
- D. interface range gigabitethernet 1/0/1-8

**Answer: C**

## Question: 2

Which command will show the policy-based routing map applied on an interface?

Response:

- A. show ip access-lists
- B. show route-map
- C. show ip policy
- D. show ip interface

**Answer: C**

## Question: 3

Which bit value is commonly used to indicate video traffic when implementing COS prioritization?

Response:

- A. 100
- B. 101
- C. 101101
- D. 101110

**Answer: A**

### Question: 4

What is needed to allow an SSH connection to a Dell EMC N-Series switch?

Response:

- A. Enable authentication, authorization, and accounting
- B. Create a default-gateway address and a static route
- C. Disable telnet and enable SSH
- D. Enable SSH and create a local user account with a password

**Answer: D**

### Question: 5

When using LLDP for configuration communication, what additional protocol features should be enabled to allow the switch to share all VoIP related parameters?

Response:

- A. lldp notification, lldp transmit-mgmt, and lldp transmit-tlv sys-cap
- B. lldp med confignotification, lldp transmit-tlv sys-cap, and lldp transmit-mgmt
- C. lldp transmit-tlv sys-cap, lldp med confignotification, and lldp notification
- D. lldp transmit-mgmt, lldp notification, and lldp med confignotification

**Answer: D**

### Question: 6

In a traditional three-tier hierarchical campus network, what are connected at the Access layer?

Response:

- A. Application servers
- B. Wireless access points
- C. Data storage devices
- D. Firewalls

**Answer: B**

### Question: 7

How many ACLs are supported on a single interface in Dell EMC switches?

Response:

- A. One ACL in only one direction
- B. One ACL in either direction
- C. Two ACLs in either direction
- D. No limit of ACLS per interface

**Answer: B**

### Question: 8

An administrator is attempting to configure MLAG on two pairs of stacked switches; however, the MLAG cannot be created. What is the most likely reason for this issue?

Response:

- A. Stacked switches cannot perform MLAG functions
- B. Stacked switches are in a Daisy Chain topology
- C. Firmware on the MLAG stacks are at different versions
- D. Spanning tree is not enabled on the MLAG stacks

**Answer: A**

### Question: 9

A port has been configured with port-security dynamic with one allowable MAC address. What happens if no frames from that MAC address are seen by the switch within the MAC table age-out time?

Response:

- A. Switch will allow the next MAC address it sees to have access on that port
- B. No MAC addresses will be allowed access on that port
- C. Only the original MAC address will ever be allowed on that port
- D. All MAC addresses will be allowed access on that port

**Answer: A**

### Question: 10

Which decimal value is used to indicate Assured Forwarding when implementing DSCP prioritization?

Response:

- A. 0
- B. 5

C. 38  
D. 46

**Answer: C**



# CERTSWARRIOR

## FULL PRODUCT INCLUDES:

Money Back Guarantee



Instant Download after Purchase



90 Days Free Updates



PDF Format Digital Download



24/7 Live Chat Support



Latest Syllabus Updates



For More Information – Visit link below:

**<https://www.certswarrior.com>**

**16 USD Discount Coupon Code: U89DY2AQ**