



CERTSWARRIOR

Dell EMC D-PDC-DY-23

Dell Technologies PowerSwitch Data Center Deploy 2023

Questions&AnswersPDF

ForMoreInformation:

<https://www.certswarrior.com/>

Features:

- 90DaysFreeUpdates
- 30DaysMoneyBackGuarantee
- InstantDownloadOncePurchased
- 24/7OnlineChat Support
- ItsLatestVersion

Latest Version: 6.0

Question: 1

What do bridge protocol data units provide?

Response:

- A. Special data frames to exchange STP information
- B. Metadata transferred connecting two network bridges
- C. Configuration data exchanged during a VLTi setup
- D. Bridge information part of the LLDP protocol

Answer: A

Question: 2

Which OSPF router is responsible for originating Network Link State Advertisements?

Response:

- A. Designated Router
- B. Internal Router
- C. Area Border Router
- D. Backbone Router

Answer: A

Question: 3

A network administrator is troubleshooting a PBR implementation and needs to know how many packets have matched the route-map criteri

a. How do they view this information in OS10?

Response:

- A. OS10# show route-map
- B. OS10# show interface statistics
- C. OS10# show route-maproute-map-statistics
- D. OS10# show route-mappbr-statistics

Answer: D

Question: 4

In an NSSA, which type of LSA is used for redistribution?

Response:

- A. 3
- B. 4
- C. 5
- D. 7

Answer: D

Question: 5

What is an advantage of running LLDP?

Response:

- A. Automatic error detection and correction of the port
- B. Reduces spanning-tree convergence
- C. Provides detailed software version information
- D. Simplifies the use of network management

Answer: D

Question: 6

Which user role in OS10 has full access to all commands and exclusive access to commands that manipulate the file system?

Response:

- A. netadmin
- B. sysadmin
- C. secadmin
- D. netoperator

Answer: B

Question: 7

What must be done before configuring any routing protocol in a VRF instance?

Response:

- A. Assign an IP address to at least one of the interfaces assigned to the VRF instance
- B. Create a routing group for each VRF instance
- C. Assign each VRF instance to a routing group
- D. Nothing, VRF routing protocols are assigned automatically

Answer: A

Question: 8

The VLAN tag is located between which fields in the Ethernet frame?

Response:

- A. Destination MAC and Source MAC
- B. Ether Type/Size and Data
- C. Preamble and Destination MAC
- D. Source MAC and Ether Type/Size

Answer: D

Question: 9

A network administrator needs to restrict packets that are destined to the CPU of an OS10 switch. How do they accomplish this?

Response:

- A. IP fragment ACLs
- B. Control-plane ACLs
- C. Management-plane ACLs
- D. Static null routes

Answer: B

Question: 10

What configuration must be common on iBGP neighbors to form an iBGP adjacency?

Response:

- A. Local preference
- B. Router-ID
- C. AS number

D. Loopback interfaces

Answer: C



CERTSWARRIOR

FULL PRODUCT INCLUDES:

Money Back Guarantee



Instant Download after Purchase



90 Days Free Updates



PDF Format Digital Download



24/7 Live Chat Support



Latest Syllabus Updates



For More Information – Visit link below:

<https://www.certswarrior.com>

16 USD Discount Coupon Code: U89DY2AQ