



CERTSWARRIOR

Juniper JN0-281

Data Center Associate (JNCIA-DC)

Questions&AnswersPDF

ForMoreInformation:

<https://www.certsvarrior.com/>

Features:

- 90DaysFreeUpdates
- 30DaysMoneyBackGuarantee
- InstantDownloadOncePurchased
- 24/7OnlineChat Support
- ItsLatestVersion

Latest Version: 6.0

Question: 1

EVPN/VXLAN is primarily used in modern data centers to:
Response:

- A. Increase the physical distance between data centers.
- B. Provide Layer 2 connectivity over a Layer 3 network.
- C. Replace traditional routing protocols.
- D. Enhance the physical security of the data center.

Answer: B

Question: 2

With regards to graceful restart, which two statements are true?
(Choose two.)
Response:

- A. A supported routing protocol, such as BGP, must be operational for graceful restart to work.
- B. NSR must be enabled for graceful restart to work.
- C. Dual routing engines are required for graceful restart to work.
- D. The network topology must be stable for graceful restart to work.

Answer: A,D

Question: 3

Which two statements are correct about aggregated Ethernet bundles?
(Choose two.)
Response:

- A. You must enable the chassis to support aggregated Ethernet interfaces.
- B. You must purchase a services license for the chassis to support aggregate Ethernet interfaces.
- C. You must specify which interfaces are members of a specific aggregated Ethernet bundle.
- D. You must enable LACP when configuring aggregated Ethernet bundles.

Answer: A,C

Question: 4

Which two protocols can you use for a data center underlay network?

(Choose two)

Response:

- A. EBGp
- B. OSPF
- C. VXLAN
- D. EVpN

Answer: A,B

Question: 5

In the Junos OS, what is the default behavior of a switch when it receives a frame with an unknown destination MAC address?

Response:

- A. It discards the frame.
- B. It floods the frame out of all ports except the one it was received on.
- C. It sends the frame to its default gateway.
- D. It buffers the frame until the MAC address can be learned.

Answer: B

Question: 6

What are two common reasons for BGP routes to be in the hidden state?

(Choose two.)

Response:

- A. Routes are being rejected by a policy
- B. Routes are being filtered from the inet.2 routing table
- C. The next hop is unresolvable
- D. The BGP neighbor is in a different autonomous system

Answer: A,C

Question: 7

Under which Junos hierarchy is a static route configured?

Response:

- A. system
- B. routing-instances
- C. routing-options
- D. protocols

Answer: C

Question: 8

How does a layer 2 switch populate its bridge table?

Response:

- A. It stores the protocol number of frames traversing the network.
- B. It stores both the source and destination MAC addresses of frames traversing the network.
- C. It stores the destination MAC address of frames traversing the network.
- D. It stores the source MAC address of frames traversing the network.

Answer: D

Question: 9

You have configured a load balancing policy. Which statement is correct about applying the policy?

Response:

- A. The policy is applied as an export policy under the routing protocol's hierarchy.
- B. The policy is applied as an export policy under routing-options forwarding table.
- C. The policy is applied as an import policy under the routing protocol's hierarchy.
- D. The policy is applied as an import policy under routing-options forwarding table.

Answer: B

Question: 10

In the context of data center networking, what is the primary purpose of an Underlay Network?

Response:

- A. To provide a physical infrastructure for an Overlay Network.
- B. To handle external network connections exclusively.

- C. To facilitate virtual machine migrations.
- D. To encrypt data traffic between servers.

Answer: A



CERTSWARRIOR

FULL PRODUCT INCLUDES:

Money Back Guarantee



Instant Download after Purchase



90 Days Free Updates



PDF Format Digital Download



24/7 Live Chat Support



Latest Syllabus Updates



For More Information – Visit link below:

<https://www.certswarrior.com>

16 USD Discount Coupon Code: U89DY2AQ